Avery Weigh-Tronix



TORSION BASES

IP69K stainless steel torsion bench bases designed for use within the food industry.





DESCRIPTION

Certified by NSF to NSF/ANSI Standard 3-A, the IP69K torsion bases are ideal bench bases for use within all types of food environments.

The rugged torsion base design and innovative Breakaway Load Transfer system help to transfer shock loads and overloads away from the load cell, offering up to 500%

overload protection and guaranteeing accuracy and reliability even in the toughest environments.

Legal for trade and available in a range of base sizes, accuracies and capacities, this fully washdown IP69K torsion bench base is stainless steel and constructed with minimal food trap areas for ease of cleaning.

SPECIFICATIONS

PHYSICAL

Operating Application	Designed to operate in a wide range of food processing environments, from meat, fish, poultry and dairy to dry food applications.			
Load Cell	Fitted with fully stainless steel 3000d BSG & 5000d BSF approved NTEP /C3 R60 approved load cell that when fitting inside the Torsion base design provides full IP69K wash-down protection. Supplied with a 6 wire 10 ft (3 meter) long load cell cable			
Base Construction	IP9K easy-to-clean, certified by NSF to NSF/ANSI Standard 3-A. Full stainless steel design, constructed from a food- grade 304 brushed base with a pickle and electro polish weigh pan ideal for food contact areas. Designed with a breakaway load transfer system to help fully protect the load cells from unwanted overloads and shock loads.			
Operating Temperature	Compliance with legal for trade requirements -4° F to 140° F / -20° C to 60° C (industrial) 10 to 90% humidity			
Load Cell Output	2 mV/V	e Carl		
Feet Adjustment	Captive thread food grade feet with up to ¼" (6mm) foot adjustment	11 35		
Overload Protection	500%			
Corner Loading	100%	6//		
IP Protection	Two torsion bench base models: Torsion base BSG 3000d, IP69K Torsion base BSF 5000d, IP69K	V		



Base construction

BSF/BSG TORSION BASES Technical Specification


BASE CAPACITY/RESOLUTION	Base size	Resolution (North America)	Resolution (Europe)	
BSG 3000d Torsion base IP69K	8.75" x 8.75" (220mm x 220mm) v min 0.002 lb n max 3000d, max capacity 100 lb	6 x 0.002 lb (3 x 0.001kg) 12 x 0.005 lb (6 x 0.002 kg)	3 x 0.001 kg 6 x 0.002 kg	
	12" x 14" (310mm x 350mm) v min 0.01 lb n max 3000d, max capacity 100 lb	30 x 0.01 lb (15 x 0.005 kg) 60 x 0.02 lb (30 x 0.01 kg) 100 x 0.05 lb (45 x 0.02 kg)	15 x 0.005 kg 30 x 0.01 kg 50 x 0.02 kg	
BSF 5000d Torsion base IP69K	8.75" x 8.75" (220mm x 220mm)	5 x 0.001 lb (2.5 x 0.005 kg) 10 x 0.002 lb (5 x 0.001 kg)		
	12" x 14" (310mm x 350mm)	25 x 0.005 lb (10 x 0.002 kg) 50 x 0.01 lb (25 x 0.005 kg) 100 x 0.02 lb (45 x 0.01 kg)		

DIMENSIONS (inches)

Base Size

8.75" x 8.75"	3.70	8.75	8.75	6.63	6.63
12" x 14"	4.30	13.75	12.25	10	11.50
DIMENSIONS (mm)					
Base Size	а	b	С	d	е
220mm x 220mm	94	222	222	168	168
310mm x 350mm	110	349	311	225	292

b



Approved Accuracy

Model BSG 3000d NTEP (3000d EC /OIML) Model BSF 5000d NTEP and Measurement Canada (3000d EC/ OIML)

APPROVALS

Agencies

NTEP (US) Class 111/IIIL 5,000 d (BSF: CC# 11-035); (BSG: CC# 03-067) AM (Measurement Canada) (BSF: AM# 5864) OIML / EC Class III 3,000 d Certified by NSF to NSF/ANSI Standard 3-A 14159-1-2010 IP69K approved









Measurement Canada Approved



www.averyweigh-tronix.com

Avery Weigh-Tronix is an ITW company

