



## DESCRIPTION

### General

Since its introduction over two decades ago, the ProDec has become the benchmark for robustness, quality and affordability. Revered by market insiders for its impressive craftsmanship, the ProDec is known as the workhorse of the industry, withstanding many hours of use with minimal downtime. The high uptime is a key reason for thousands of ProDec installations at locations requiring around the clock functionality to optimize operations while reducing costly downtime.

### Design

**Low profile design** – The height of 3.31 inches on the 5,000 lb model, 4.06 inches on the 10,000 lb model and 5.00 inches on the 20,000 lb model allow for easy loading and unloading.

**Exclusively designed Weigh Bars®** – The Weigh Bar outperforms most shear beam load cells in accuracy and reliability due to its low V min. When fitted with a Weigh Bar, the ProDec will perform as fast, as stable and as accurately in a 5,000 lb setup as it does in a 10,000 lb capacity. This provides our customers with a higher strength deck and the flexibility to lower the legal-for-trade capacity and resolution without losing accuracy or performance.

**Unsurpassed rigidity** – The ProDec is engineered to provide outstanding strength and robustness at all times with its steel support channel understructure welded to a  $\frac{3}{16}$ " top plate in the 2,000/5,000 lb capacity scale while the 10,000 lb/20,000 capacity has a  $\frac{1}{4}$ " top plate – this helps to keep the deck from warping and bending.

**Serviceability** – Hidden under an easily removable access plate in the top deck structure, the ProDec's junction box can be easily accessed for servicing but remains well protected from damage.

**Four-way ramps** – Ramps can be placed to speed up workflow from multiple directions and improve efficiency for many applications.

**Tread plate deck texture** – This deck texture pattern provides higher traction than non-checked designs and reduces the risk for slip and fall accidents.

**Adjustable feet** – The corrosion resistant stainless steel feet with locking nuts are adjustable and allow for leveling between  $\frac{3}{8}$ " to  $\frac{1}{2}$ ".

**End loading** – The ProDec is designed to accommodate some of the most unique weighing situations. The ProDec has an end loading rating of 200% at a 2,000 lb, 150% at 5,000 lb and 100% for the 10,000 lb and 20,000 lb.

**Axle loading** – The ProDec axle load ratings are: 3,300 lb for a 5,000 lb scale; 5,000 lb for 10,000 lb capacity; and 10,000 lb for 20,000 lb capacity scales.

# ProDec DSL Series FLOOR SCALE *Technical Specification*

## STANDARD SIZES, CAPACITIES AND FINISHES

	Model No.	Dimensions	Powder Coat	Urethane Finish
2,000 / 5,000 lb (1000 / 2500 kg)	DSL3030-05	30 x 30 x 3.31 in (76 x 76 x 8.4 cm)	X	
	DSL3636-05	36 x 36 x 3.31 in (91 x 91 x 8.4 cm)	X	
	DSL4848-05	48 x 48 x 3.31 in (122 x 122 x 8.4 cm)	X	
	DSL6048-05	60 x 48 x 3.31 in (152 x 122 x 8.4 cm)	X	
	DSL7248-05	72 x 48 x 3.31 in (186 x 122 x 8.4 cm)	X	
	DSL6060-05	60 x 60 x 3.31 in (152 x 152 x 8.4 cm)	X	
5,000 / 10,000 lb (2500 / 5000 kg)	DSL4848-10	48 x 48 x 4.06 in (122 x 122 x 10.3 cm)	X	
	DSL6048-10	60 x 48 x 4.06 in (152 x 122 x 10.3 cm)	X	
	DSL7248-10	72 x 48 x 4.06 in (183 x 122 x 10.3 cm)	X	
	DSL6060-10	60 x 60 x 4.06 in (152 x 152 x 10.3 cm)		X
	DSL7260-10	72 x 60 x 4.06 in (183 x 152 x 10.3 cm)		X
	DSL8460-10	84 x 60 x 4.06 in (213 x 152 x 10.3 cm)		X
	DSL8472-10	84 x 72 x 4.06 in (213 x 183 x 10.3 cm)		X
	DSL9672-10	96 x 72 x 4.06 in (244 x 183 x 10.3 cm)		X
10,000 / 20,000 lb (5000 / 10,000 kg)	DSL6060-20	60 x 60 x 5.00 in (152 x 152 x 12.7 cm)		X
	DSL8460-20	84 x 60 x 5.00 in (213 x 152 x 12.7 cm)		X
	DSL9672-20	96 x 72 x 5.00 in (244 x 183 x 12.7 cm)		X

## SPECIFICATIONS

### GENERAL

<b>Construction</b>	Welded support channels. All cables protected within the deck to eliminate potential damage to wiring 2,000/5,000 lb capacity: 3/16" top plate 10,000 lb/20,000 lb capacity: 1/4" top plate
<b>Lifting Positions</b>	48" or less – one lifting eye on each of the two short sides of the scale. Over 48" – two lifting eyes each on each of the two short sides of the scale
<b>Lifting Eye Size</b>	0.50-13 UNC
<b>Weight Sensors</b>	Four Weigh Bars
<b>Weigh Bar Output</b>	2,000 lb capacity: 0.54 mv/v 5,000 lb, 10,000 lb and 20,000 lb capacity: 1.35 mv/v
<b>Overload Protection</b>	150%
<b>End Loading</b>	The end load ratings vary by capacity: 200% at 2,000 lb, 150% at 5,000 lb, and 100% for the 10,000 lb and 20,000 lb capacities
<b>Accuracy</b>	Meets or exceeds NTEP Class III 5,000 division accuracy
<b>Operating Temperature</b>	14° to 104°F (-10° to 40°C)
<b>Interface Cable</b>	25 ft cable included
<b>Agencies</b>	NTEP (CC# 90-132.A2) Measurement Canada Factory Mutual (FM) approved Weigh Bars and junction box when connected to the ZM155 Indicator. Suitable for Class I, II, III Divisions 1 & 2; Groups A, B, C, D, E, F, G. For Hazardous Area applications, contact the Avery Weigh-Tronix Industrial Support group for assistance with Class I, II, III Div. 1 & 2 barrier options with safe area ZM Indicators.

### SHIPPING WEIGHTS

Model No.	Carbon Steel
DSL3030-05	176 lb (80 kg)
DSL3636-05	223 lb (101 kg)
DSL3636-02	162 lb (73 kg)
DSL4848-05	338 lb (154 kg)
DSL6048-05	391 lb (178 kg)
DSL7248-05	456 lb (207 kg)
DSL6060-05	484 lb (220 kg)
DSL4848-10	491 lb (223 kg)
DSL6048-10	566 lb (257 kg)
DSL7248-10	641 lb (291 kg)
DSL6060-10	679 lb (309 kg)
DSL7260-10	772 lb (351 kg)
DSL8460-10	910 lb (414 kg)
DSL8472-10	1,027 lb (467 kg)
DSL9672-10	1,133 lb (515 kg)
DSL6060-20	850 lb (385 kg)
DSL8460-20	1,140 lb (517 kg)
DSL9672-20	1,420 lb (644 kg)



Measurement  
Canada Approved

# Avery Weigh-Tronix

[www.averyweigh-tronix.com](http://www.averyweigh-tronix.com)

Avery Weigh-Tronix is an ITW company



Avery Weigh-Tronix is a trademark of the Illinois Tool Works group of companies whose ultimate parent company is Illinois Tool Works Inc ("Illinois Tool Works"). Copyright © 2020 Illinois Tool Works. All rights reserved. This publication is issued to provide outline information only and may not be regarded as a representation relating to the products or services concerned. This publication was correct at the time of going to print, however Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service at any time.

ProDecDSL\_spec\_500476.indd  
V3 AWT35-500476