

# DILLON

Force Measurement Equipment

## *ED Series Crane Scales*

EDxtreme & EDjunior Crane Scales



# Dillon ED Series Crane Scales

## Advanced Weighing

**Guesswork is not acceptable.** When you have people working around high tension cables and massive loads, there is no room for error. You have to have complete confidence in the strength and the accuracy of your measurement tools.

Since 1937, Dillon dynamometers have been chosen for the jobs where only the best will do. Now, Dillon has once again lifted the performance bar and set the standards for others to follow - Dillon ED Series Crane Scales.

**Two ED Series models are available:** The **high-end ED Xtreme** (also called EDX), and the **affordable ED Junior**. Choose ED Xtreme for the most demanding applications; ED Xtreme is built with the best materials and designed with cutting-edge features like radio control. Where cost is a concern, and reliability is a requirement, choose ED Junior - the perfect crane scale for simple jobs.

## ED Xtreme - The ultimate in reliability & accuracy

Popular industry – standard shackles insure proper fit

Sturdy aircraft – quality aluminium (shown) or painted alloy steel case on high capacity models

Battery compartment – easy access without tools

High-resolution dot-matrix LCD display offers large numbers without confusing abbreviations or multipliers

Injection moulded, thick Lexan panels offer superior impact protection

Softkey interface allows easy and intuitive operation and configuration

NEMA 4X/IP55 designed for weather and water resistance



All ED Xtreme Crane Scales include storage crate, instructions, and certificate of calibration.



### Hook Choices

Reliable, high quality Crosby hooks are used on all EDX Crane Scales.

- **Non-Swivel Hook (left)** - Basic hook for low-cost, low-headroom weighing.
- **Basic Swivel Hook (center)** - Used to align rigging to the crane.
- **Bearing Swivel Hook (right)** - Used for precise positioning under load.

Capacities available from  
2500 lbf to 50,000 lbf  
(1000 kgf to 20000 kgf)

# EDXtreme - Signature features

## Xtreme Engineering

Building a precision instrument that can survive real-world punishment requires masterful engineering. This is where Dillon's experience shines through. The engineers assigned to the EDXtreme drew on a depth of industrial application knowledge and conducted exhaustive materials testing to achieve the highest structural integrity.

- **Superior strength and corrosion resistance** – High capacity models are constructed of powder coated aircraft quality alloy steel. Lower capacity models are power coated aircraft quality aluminium.
- **5:1 factor of safety** – This measure of strength and safety is maintained at all capacities (*capacities of 75T and above are 4:1 USF*). Computer modelling confirms the low stress and long product life that is inherent in the EDXtreme design.
- **Retained Hardware** – allows permanent attachment of centering spacers which eliminates fumbling during high capacity rigging.
- **NEMA 4X/IP55** – The EDXtreme is clearly the choice for readability in any environment – in plant or out on the job site.
- **Warranty** – 2 years parts and labor

## Xtreme Accuracy

High resolution and accurate repeatable readings are essential to proper weighing. The higher standards set for the EDXtreme meant taking the time to ensure that material characteristics, load element design and strain gage meshed perfectly. The result of that effort is a typical accuracy of 0.1% of capacity up to EDX-50T and 0.3% of capacity for EDX-75T and above. The enhanced resolution mode of 1 part in 5000 provides the level of readability needed for refined weighing.

## Xtreme Ease

- **Exclusive SOFTKEY interface** – Eliminates confusing menus for faster setup and simple operation.
- **Local gravity correction** – Unit adjusts to local gravitational conditions, without recalibration.
- **Custom units of measure** – User-defined units of measure mean the instrument adapts to changing requirements.
- **Wide-angle, backlit LCD** – Provides improved readability over a wider viewing angle and has backlighting for low light conditions.
- **Battery operation** – Powered by two standard C-cell batteries. Batteries are easily accessible for fast replacement.

## Expandable Scale Network

A basic stand alone model can be easily upgraded "in-the-field" to accommodate changing needs. Remote configuration, data acquisition and single point monitoring of multiple links are all possible with the hardwired or radio communication option with the EDXtreme.

Optional Remote Communicator, showing four crane scale readings and total of all.



## Typical Configuration

1. Stand alone EDXtreme for simple, direct measurement applications.
2. Single network with one EDXtreme radio dynamometer and optional Communicator.
3. Single network with multiple EDXtreme radio dynamometers and one optional Communicator. The Communicator offers the ability to monitor the load at each link as well as a viewing the total weight of multiple dynamometers.
4. Multiple network with multiple EDXtreme radio dynamometers and Communicators.



An RS-232 interface is standard on both the EDXtreme and Communicator for connection to a host PC.

KEY:   plant airspace   discrete radio channel

# EDjunior - The market leader in accuracy & value

The EDjunior is all about value. Behind its simple design and easy operation, you will find the quality and performance not found elsewhere. With the EDjunior, Dillon proves that economy can go hand-in-hand with accuracy, long service life and, most importantly, worker safety – just compare the Dillon EDjunior to the competition. Nothing else comes close!

## Measurement Capabilities

The EDjunior provides peak detection as well as live load readings. Selectable units of measure include lbf, kgf and Newtons.

**Accuracy** — The load element design and strain gauges chosen for the EDjunior produce an accuracy of 0.2 % (full scale). This level of precision offers flexibility for use in a broad range of applications. Capacities up to 10,000 lb (5000 kg) available.

**Resolution** — Readings are displayed with a resolution of 1 part in 1000 to ensure the level of readability required for critical lifting applications.

## Control Interface

The exclusive Dillon SOFTKEY interface provides direct access to setup and display functions without the typical confusing menu structure. The 6-digit dot-matrix display features 1 inch (25 mm) high numerals for greater visibility.

## High Strength, Low Weight

Heavy, cumbersome tools make tough jobs even harder. Through the use of aircraft quality materials, Dillon has made the EDjunior an easy-to-position, highly mobile instrument with exceptional strength. It offers an impressive factor of safety at all capacities.

## All Environments

With its NEMA 4/IP55 design, the EDjunior is at home in virtually any environment and ideally-suited to outdoor job-site applications as well as in-plant use.



## Hook Choices


Reliable, high quality Crosby hooks are used on all EDX Crane Scales.

- **Non-Swivel Hook (left)** - Basic hook for low-cost, low-headroom weighing.
- **Basic Swivel Hook (right)** - Used to align rigging to the crane.



## Dillon on the job

Dillon force measurement equipment is the preferred choice of public utilities, nuclear facilities, tower erectors, armed services and material handlers throughout the world. In addition to the EDXtreme, Dillon's electronic line includes the EDjunior, an exceptional value for basic applications. Dillon also manufactures crane scales, high accuracy mechanical dynamometers and overload protection devices.



## DILLON

Force Measurement Equipment  
A division of Avery Weigh-Tronix, LLC

Foundry Lane, Smethwick,  
West Midlands B66 2LP

Tel: +44 (0) 845 246 6717 Fax: +44 (0) 845 246 6718

E-mail: [sales@dillon-force.co.uk](mailto:sales@dillon-force.co.uk)

[www.dillon-force.co.uk](http://www.dillon-force.co.uk)

© Avery Weigh-Tronix 2010. All rights reserved. This publication is issued to provide outline information only which, unless agreed by Avery Weigh-Tronix in writing, may not be regarded as a representation relating to the products or services concerned. Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

6/10 EDcrane\_RoW\_L\_500597.indd  
AWT35-500597 (web 6/12)