## **Avery Weigh-Tronix**



# FORKLIFT SCALE SYSTEM

(non legal-for-trade)

Technical Specification





### **DESCRIPTION**

#### General

The Avery Weigh-Tronix QTLTS Forklift Scale System turns a lift truck into a mobile scale. The system includes a durable, front-mounted digital scale carriage with Weigh Bar® electronic weight sensors and two viewing ports. The system allows operators to easily and quickly capture weight data en route, without extra steps.

#### **Seamless Compatibility**

Simply attach the QTLTS scale carriage to an existing Class II cleat-type forklift carriage and mount the FLI 225 instrument in a convenient driver location. This system allows seamless integration of weighing and data management into your operations without adding any extra steps or route changes.

#### **Robust Design**

The forklift scale carriage is comprised of two metal plates coupled together by four high capacity Weigh Bars.

- > Front loading safety factor of 29.5:1
- Normal load safety factor of 7.5:1
- Overload with no damage of 200%

The instrumentation is designed exclusively for the forklift vehicle. It incorporates design technologies to withstand the environmental and warehouse jolts common in forklift applications.

#### Performance

The QTLTS is the solution for monitoring loads handled by forklifts that do not require legal-for-trade accuracy. The QTLTS consistently provides 99% or better weight accuracy of the applied load regardless of the position of the forks or mast. The Quick Tach scale carriage attaches to an existing forklift carriage and withstands up to 200% of full capacity applied anywhere up to 24" from the frame and side loads up to 100% of full capacity.

> ITA Class II Cleat Type - 5,000 x 1 lb

This electronic scale design has no mechanical flexures or springs to influence the weighing performance.

#### **Data Management**

The FLI 225 instrument provides a simple, no-nonsense solution through classic or enhanced operation for capturing weight and supplying it to a peripheral device.

### **QTLTS FORKLIFT SCALE** Technical Specification

#### **SCALE CARRIAGE**

Front and Back Plates Yield Strength	43,500 psi
Weigh Bar® Fasteners Yield Strength	160,000 psi
Weigh Bar Tensioners Yield Strength	150,000 psi
Mounting Hooks Yield Strength	43,500 psi
View Port	Two viewing ports
Weight Sensors	Four Avery Weigh-Tronix 2500 LB Weigh Bars direct coupled, no flexures
Overload Protection	Withstands up to 200% of full capacity applied anywhere up to 24" from frame and side loads up to 100% of full capacity
Finish	High grade powder paint
WEIGH BAR	
Туре	2.5k weight sensors (4) 5,000 LB
Metal Properties	AISI 4340 steel yield strength 140,000 psi
Zero Balance	$\pm$ 0.10 mv/v
Non-Linearity Maximum	0.3% of rated output
Hysteresis Maximum	0.03% of rated output
Temperature Effect on Output	$\pm$ 0.0025% ° C of rated output (-10 to +40° C)
Temperature Effect on Zero Balance	± 1.70 x 10-7 volts per volt 5°C (-10 to +40° C)
Safe Overload Rating	150% of capacity
WEIGHT SUMMING	
Enclosure	Metal enclosure, circuitry encapsulated
APPROVALS	
	FCC part 15B CE

#### **FLI 225 INSTRUMENT**

Туре	FLI 225 instrument NTEP CC# 07-091, category 3
Power Input	9 to 36 vdc, 3.5 Amp, Inactive stand by mode
Display	FLI 225 – High contrast backlit transflective LCD dot matrix. Custom designed font ¾"high digits. Classic, Classic with Accumulation and Expanded Modes
Operational Keys	FLI 225 - On/Off, Zero, Print, Select, Tare, F1-F4
Operational Images	FLI 225 – Weight, LB/KG, Motion, Center of Zero, Weigh mode, Operator status messages
Communication Ports	FLI 225 - Two RS 232 serial ports
Operating Environment	Legal 14° to 104° F (-10° to +40° C), industrial -20° to +60° C
Enclosure	FLI 225 - Composite with tilt and swivel brackets, designed to IP65
Dimension	FLI 225 – 8.14"W x 5.19"H x 4.03"D includes mounting bracket
Weight	FLI 225 - 4 LB / 1.8 KG
Options	FLI 225 - FLP 100 power conditioner 24 to 72 vdc, RM 100 bt (2.0)

Weigh Bar® is a registered trademark of Avery Weigh-Tronix, LLC



www.averyweigh-tronix.com

- Avery Weigh-Tronix is an ITW company

